

COMSOFT



XPS-E

PROFIBUS DP/RS232/RS422/
RS485 Gateway

Intelligent, Low-Cost PROFIBUS DP Gateway

There are still a lot of serial end devices in diverse plants, which are not compatible with PROFIBUS. It is important to integrate these devices to allow communication and data exchange and overcome the system limitations. Serial devices do not usually have their own PROFIBUS field bus interface, typically they will only have an RS232, RS422 or RS485 interface. The gateway XPS-E from COMSOFT offers the ability to connect them with the PROFIBUS in a low-cost, easy, quick and reliable way.

The XPS-E can be easily installed and is distinguished by its user friendliness. External devices, such as a serial configuration tool on a PC, are not required to carry out the configuration.

All connections are by D-SUB connectors or spring clip terminals which can all be connected and removed easily. The PROFIBUS station address is set via coding switches. The gateway is designed for hat rail installation.

All send and receive sequences of the serial devices are depicted 1:1 on the PROFIBUS. The XPS-E can be easily integrated as a PROFIBUS DP Slave via the device data base file (DDBF) in existing configurations. Thus these devices can be quickly connected to PROFIBUS networks.

The XPS-E has been established in the market since 1999 and has demonstrated its reliability in countless installations. The serial data can be accessed quickly and exactly. Our drivers, which can be customised to your special requirements, allow the pre-processing of the data in the gateway.

The gateway XPS-E allows for the cost-efficient integration of serial devices into the PROFIBUS.

The attractive price, plus the easy and quick integration into PROFIBUS networks as well as the proven reliability in countless installations speaks for itself.



Technical Data

| | | |
|--------------------------------------|---------------------------|---|
| Supported PROFIBUS Protocol Versions | DP Slave | Modular 4-240 Bytes |
| Interfaces | Serial PROFIBUS | RS232/422/485 RS485 (isolated) |
| Baud Rates | Serial PROFIBUS DP | max. 38.400 Bit/s asynchronous (adjustable via PROFIBUS) 9.6, 19.2, 93.75, 187.5, 500 Kbit/s and 1.5, 3.6, 12 Mbit/s |
| Power Supply | 24 VDC | |

Manufacturer:

COMSOFT GmbH | Wachhausstr. 5a | 76227 Karlsruhe | Germany | Tel: +49-(0)721/9497-291
Fax: +49-(0)721/9497-299 | E-mail: infoicp@comsoft.de | Internet: www.comsoft.de